

# Drain valves

## 取样阀

## Valvole di spurgo

## Entleerungsventil



### FEATURES

- Ball valve.
- Compact body.
- Available in ABS / PVC.
- Connections to rigid pipe or PE flexible pipe.
- Very useful in drain circuits.
- Working pressure: PN 6 / 10.
- Female threaded end connectors.
- BSP threaded versions.
- Threaded connections must be wrapped with Teflon tape.

### 特点

- 球阀
- 紧凑型阀体
- ABS / PVC.
- 连接到硬管上或PE弹性管上
- 在排水系统中非常有用
- 运转压强: PN 6 / 10.
- 内螺纹阀端
- BSP螺纹版本
- 牙口连接上需裹Teflon胶带

### CARATTERISTICHE

- Valvola a sfera.
- Corpo compatto.
- Disponibile in ABS / PVC.
- Connessioni con tubo rigido o con portagomma per tubo flessibile in PE.
- Molto utilizzata nei circuiti di spurgo.
- Pressione di lavoro: PN 6 / 10.
- Connessione filetto femmina.
- Versioni filettate: BSP.
- Le connessioni filettate devono sempre essere realizzate con l'utilizzo di nastri in Teflon..

### KENNDATEN

- Kugelhahn.
- Kompaktbauweise.
- In ABS / PVC erhältlich.
- Anschlussmöglichkeit für Rohre und Schläuche aus PE.
- Besonders für Entlüftungssysteme geeignet.
- Arbeitsdruck: PN 6 / 10.
- Anschluss mittels Gewindemuffen und -stutzen.
- Gewindeversionen: BSP.
- Die Verwendung von Teflonband wird empfohlen.


## ABS. 90. MT

- Drain valve
- ABS body
- BSP male thread
- Seating joints in HDPE

- 取样阀
- ABS阀体
- BSP外螺纹
- HDPE垫片

- Valvola di spurgo
- Corpo in ABS
- Filetto maschio BSP
- Guarnizione sagomata sfera in HDPE

- Entleerungsventil
- ABS Gehäuse
- Gewindemuffe BSP
- Kugelsitzdichtung HDPE



G	CODE	REF.	PN	L	L <sub>1</sub>	H	H <sub>1</sub>
1/4"	11656	05 90 612	6	54	10	10	19


## UP. 90. MT

- Drain valve
- PVC-U body
- BSP male x female thread
- Seating joints in HDPE

- 取样阀
- PVC-U阀体
- BSP外螺纹 x 内螺纹
- HDPE垫片

- Valvola di spurgo
- Corpo in PVC-U
- Filetto maschio x femmina BSP
- Guarnizione sagomata sfera in HDPE

- Entleerungsventil
- PVC-U Gehäuse
- Gewindestutzen/-muffe BSP
- Kugelsitzdichtung HDPE



G	CODE	REF.	PN	L	L <sub>1</sub>	H
3/4"	02579	05 90 625	10	12	12	50