

Sight glasses / 视镜 / Visori per liquidi / Schaugläser

UP. 54. SF

- Material:
 - D50 - D63: PMMA (Fig. A)
 - D75 - D225: SAN (Fig. B)
- 4 screws
- Female solvent socket
- Metric series

Working pressure at 20°C (73°F) water
temperature:

- D50 - D63: PN 6
- D75 - D225: PN 10

- 材质:
 - D50 - D63: PMMA (图 A)
 - D75 - D225: SAN (图 B)
- 4颗螺丝
- 平口连接
- 公制系列

工作压力20°C (73°F)
水温:

- D50 - D63: PN 6
- D75 - D225: PN 10

- Materiali:
 - D50 - D63: PMMA (Fig. A)
 - D75 - D225: SAN (Fig. B)
- 4 viti
- Incollaggio femmina
- Serie metrica


Pressione di servizio 20°C (73°F)
temperatura dell'acqua:

- D50 - D63: PN 6
- D75 - D225: PN 10


- Material:
 - D50 - D63: PMMA (Fig. A)
 - D75 - D225: SAN (Fig. B)
- 4 Schrauben
- Klebemuffen-Anschluss
- Metrische Serie

Arbeitsdruck bei 20°C (73°F)
Wassertemperatur:

- D50 - D63: PN 6
- D75 - D225: PN 10



A



B



D	CODE	REF.	DN	L	H	E	MOD.
50	02387	05 54 050	40	31	130	80	A
63	02388	05 54 063	50	38	159	92	A
75	02389	05 54 075	65	44	165	185	B
90	02390	05 54 090	80	51	180	200	B
110	02391	05 54 110	100	61	250	220	B
125	02392	05 54 125	110	69	280	230	B
140	02393	05 54 140	125	76	310	250	B
160	02394	05 54 160	150	86	360	285	B
200	02395	05 54 200	175	106	420	315	B
225	02396	05 54 225	200	119	500	340	B

UP. 54. FT

- Material: PMMA
- 4 Screws
- BSP female thread

Working pressure at 20°C (73°F)
water temperature:

- 1½" - 2" PN 6

- 材质: PMMA
- 4颗螺丝
- BSP内螺纹

工作压力20°C (73°F)
水温:

- 1½" - 2" PN 6

- Materiali: PMMA
- 4 viti
- Filetto femmina BSP


Pressione di servizio 20°C (73°F)
temperatura dell'acqua:

- 1½" - 2" PN 6

- Material: PMMA
- 4 Schrauben
- Anschluss Innengewinde BSP

Arbeitsdruck bei 20°C (73°F)
Wassertemperatur:

- 1½" - 2" PN 6



D	CODE	REF.	DN	L	H	E
1½"	02397	05 54 650	40	31	130	80
2"	02398	05 54 663	50	38	159	92

注: PMMA: 聚甲基丙烯酸甲酯
SAN: 苯乙烯丙烯腈共聚树脂